

Anker SOLIX C1000X Portable Power Station

1056Wh | 1800W

InfiniPower™ GaNPrime™



TotalGuard™

SurgePad™

*Full Speed to Go ,
Full Power to Last*



Highlights

InfiniPower™ 10 Years of Everyday Use

LiFePO4 batteries offer a 6× longer lifespan than the average power station. Designed for a decade of daily use, with an industry-leading 5-year device warranty

HyperFlash™ Fast Recharge

You don't have a second to waste. Whether you've got a big trip or bad weather is on the horizon, Anker SOLIX C1000X recharges to 100% in just 58 minutes.* That's 27.5% faster than power stations with the same capacity for ultra-fast, worry-free recharging.

Power Anything with SurgePad™ Technology

Sip on freshly brewed coffee and grill up breakfast at the same time. With SurgePad™ Technology, You have up to 2400W output that powers 99% of appliances.



Features

Proven Durability TotalGuard™

Our drop-proof design and material selection meet the requirements of industry testing standards to withstand any impact during outdoor adventures.

Pro UPS

Ensure continuous power with Uninterruptible Power Supply (UPS) Switchover time in under 20ms.

15% Smaller Than Industry Average

You don't need to do any heavy lifting. Anker SOLIX C1000X is more compact and just as powerful as similar-capacity LFP power stations.

Flat Top for Extra Space

Give yourself some extra room thanks to the flat design of Anker SOLIX C1000X. You can set your devices or batteries on top, just like a desk.

Specifications

Product Model

PN	A1761
Model Name	Anker SOLIX C1000X Portable Power Station

Battery Info

Type of Battery	LiFePO4
Capacity	1056Wh
Capacity	330000mAh
Cycle Life	3000+ (to 80%)



Specifications

Power Outputs

Maximum Output	1800W
# of Output Ports	11 (For US/JP/CA); 9 (For EU/UK/MEA/AU/CN)
# of Standard AC Socket	6 (For US/JP/CA) ; 4 (For EU/UK/MEA/AU/CN)
AC Rated Power	1800W
AC Surge Power	2400W
AC Total Output	1800W; Surgepad 2400W
AC Auto Shut-Off	standby mode 12h
# of USB-A Output	2

USB-A Rated Power (per port)	5V=2.4A (12W Max)
USB-A Total Output	24W
# of USB-C Output	2
USB-C Rated Power (per port)	5V=3A/ 9V=3A/ 12V=2.5A (30W Max) 5V=3A/9V=3A/15V=3A/
USB-C Total Output	130W
USB auto shut-off	Yes
# of Car Outlet	1
Car Outlet Rated Power (per port)	10.8~14V=10A (120W Max)

Specifications

Power Inputs

Input Voltage	100-120V (US/CA/JP) 220-240V (UK/EU/MEA/CN/AU)
Total Input Power	1300W (AC Direct)
EST Recharge Time	Default AC recharging: 90min(1000W) Ultra Fast AC recharging: 58min(1300W) Car socket recharging: 10.7h(120W) solar recharging: 1.8h(600W)
Use Ports While Recharging	Yes
Direct AC Input	Yes
Maximum AC Input Power	1300W
# of DC Input	1
DC Adapter	No
DC Adapter Input Power	-

EST DC Adapter Recharge Time	10.7 hrs (120W Car Charger)
DC Input Size	XT-60
Solar Input Power	11-32V $\equiv$ 10A; 32V-60V $\equiv$ 12.5A (600W Max)
EST Solar Recharge Time	6.1 Hours (2*100W) 4 Hours(3*100W) 3.6 Hours(2*200W) 2 Hours(3*200W) 1.8 Hours (2*400W)
Solar Panel Compatible	Yes
MPPT Support	Yes

Specifications

Illumination Information

Flash Light	-
Flash Light Mode	-
Ambient Light	Yes
Ambient Light Mode	Ambient Light Mode (3 Level) SOS Mode

Safety Information

Operation Temperature (°C/°F)	Charging: -20 -40°C / -4 -104°F Recharging: 0-40°C / 32-104°F
Overload Protection (AC)	>1800W
Over-current Protection (USB-A)	>2.4A >3.6A (30W)
Over-current Protection (USB-C)	>6A (100W)
Over-current Protection (Car port)	>10A

Package Content

AC Adapter	-
Cable	AC Charging Cable 150cm Car Charging Cable 300cm Solar Charging Cable (1 to 2) 170cm

Weight & Dimension

Product Dimension (mm)	376x205x267 mm
Packaging Dimension	Packaging 451x274x310mm UN BOX 464x287x330mm
Product Weight	12.9 kg ; 28.44 lb
Product Weight with Package	14.1 kg ; 31.09 lb